

Indoor Air Quality Test Kits

Specification Sheet

Portable and accurate real-time air quality information, made affordable

Easy-to-use air quality monitoring kits with everything required to start measuring common indoor pollutants, or for checking compliance to the WELL Building Standard™ (WELL).

Expand the kits at any time from our wide range of sensor heads for different gases, or customize a kit to suit your requirements.

Can also be used outdoors.



Kits at a glance

Kit / Contents	Aeroqual Ranger Monitor	Sensors				
		PMX	CO ₂	VOC	CO	O ₃
IAQ Starter	✓	✓	✓	GSS		
IAQ Pro	✓	✓	✓	PID	✓	
WELL	✓	✓			✓	✓

Who are they for?

- **Health and safety managers** who need to demonstrate safe environments
- **Researchers** who want to collect scientifically robust data on a limited budget
- **Air quality professionals** who need real-time measurements
- **Educators** who want students to learn about air pollution in a way that supports STEM

What are they for?

- Indoor air quality assessments
- Personal exposure checks
- Health and safety compliance
- Health and comfort assessment
- Checking indoor air pollution “hotspots”
- HVAC system performance monitoring
- Indoor air quality studies
- WELL Compliance assessments

Specifications | Indoor Air Quality Test Kits

Sensor specifications

Gas module & Particulate Sensors	Range	Sensor Type*	Minimum Detection Limit	Accuracy of Factory Calibration	Resolution	Response Time	Temperature	Relative Humidity	Kit		
									STR	PRO	WELL
PMX Particulate Matter (PM ₁₀ , PM _{2.5} , PM ₄ , PM _{10T} , TSP)	0-30.0 mg/m ³	LPC	Zero stability ± 0.1 µg/m ³	<±8% of reading	0.1 µg/m ³	1 Second	0 to 40°C	0 to 95%	✓	✓	✓
Ozone (O ₃)	0-0.5 ppm	GSS	0.001 ppm	<±0.008 ppm 0-0.1 ppm <±10% 0.1-0.5 ppm	0.001 ppm	60 Seconds	0 to 40°C	10 to 90%		✓	✓
Carbon Dioxide (CO ₂)	0-5000 ppm	NDIR	20 ppm	<±20 ppm + 5%	1 ppm	120 Seconds	0 to 40°C	15 to 90%	✓	✓	
Carbon Monoxide (CO)	0-100 ppm	GSE	0.2 ppm	<±1 ppm 0-10 ppm <±10% ppm 10-100 ppm	0.1 ppm	30 Seconds	0 to 40°C	15 to 90%		✓	
Carbon Monoxide (CO)	0-25 ppm	GSE	0.05 ppm	<±0.5 ppm 0-05 ppm	0.01 ppm	60 Seconds	0 to 40°C	15 to 90%			✓
				<±10% 5-25 ppm							
VOC	0-25 ppm	GSS	0.1 ppm	<±0.1ppm + 10%	0.1 ppm	60 Seconds	0 to 40°C	15 to 95%	✓		
VOC	0-20 ppm	PID	0.01 ppm	<±0.2ppm + 10%	0.01 ppm	30 Seconds	0 to 40°C	0 to 95%		✓	

* Sensor Types: Gas Sensitive Semiconductor (GSS), Gas Sensitive Electrochemical (GSE), LaserParticle Counter (LPC), Photoionization Detector (PID). For the full range of available sensors, visit our website; www.aeroqual.com or [download the list](#).

Monitor specifications

Aeroqual Ranger portable monitor system specifications (Included in Starter & Pro Air Testing Kits)	
Measurement units	PM: mg/m ³ , µg/m ³ Gas: ppm, ppb, mg/m ³ , µg/m ³ Relative Humidity: % Temperature °C or °F
Displayed measurements	Instantaneous, 1-minute and 5-minute averaged concentration AQI for PM2.5 (Cal/OSHA)
Field calibration	Gas sensors: Zero and Span PM sensor: Zero, Span and Flow
Factory calibration	Traceable certified calibration certificate valid for 1 year Hot-swap sensor option available. Hot swap is a factory calibration program that delivers a factory-calibrated sensor head to you without the hassle of sending your old one back (see Aeroqual distributor)
Environmental operating conditions and Ingress Protection	Temperature: -10°C to 40°C (14°F to 104°F) Humidity: 0 to 95% RH non-condensing IP Rating: IP20
Power	Battery type: Lithium Ion Battery life: >20 hours Charger connector: USB-C Recharge time: approximately 4.5 hours
Data logging	Storage: 5 years on-board Logging interval: 60 seconds
Software	Aeroqual Cloud for Ranger
Data connectivity	Wi-Fi, USB-C cable file download, Analogue 0-5v output
Physical characteristics	Size: 170 x 83 x 37 mm (6¾" x 3¼" x 1½") Weight: 430g (15 oz)
Compliance	IEC/EN 61326-1 EN 55011:2010 AS/NZS CISPR 11:2011 IEC/CISPR 11:Ed.5.1 FCC Part 15 IEC 61010-1:2010+A1:2016AU/NZ: AS 61010.1; Europe: EN 61010-1:2010 + A1:2019; Canada: CAN/CSA-C22.2 No. 61010-1-12 3rd Edition; USA: UL 61010-1 3rd Edition RoHS 3 (EU 2015/863), REACH

Specifications are subject to change without notice.

Aeroqual is an ISO 9001 certified company.
Aeroqual and Aeroqual Ranger are registered trademarks of Aeroqual Limited.

