

Series 900/930/SM70

Specification Sheet



Series 900



Series 930

Shown with optional LED display, strobe and siren



SM70 Fixed Monitor

Aeroqual fixed indoor air quality monitors are designed to make indoor air quality monitoring easy. They are used by researchers, professionals, and non-experts alike to gather indoor air quality data from indoor environments. Commercially they are used for ozone generator control, process control, monitoring controlled atmospheres, air quality, and health and safety compliance.

Monitors at a glance

| Features / Series | 900 | 930 | SM70 |
|--|--------------|-------------|---|
| Active fan sampling | ✓ | ✓ | ✓ |
| PC data logging and real-time network capability | ✓ | ✓ | |
| Multiple analogue and digital outputs | ✓ | ✓ | ✓ |
| Interchangeable sensor heads | All gases | Some gases | Replaceable (O ₃ sensor board) |
| Enclosure | IP20/ NEMA 1 | IP41/NEMA 2 | IP20/ NEMA 1 |
| Options | 900 | 930 | SM70 |
| Temperature and RH sensor | ✓ | ✓ | |
| Large LED display | | ✓ | (Built-in 3.5 digit LCD) |
| Strobe and siren | | ✓ | Buzzer alarm |

Monitors at a glance

Aeroqual uses a unique system of interchangeable sensors making it simple to replace one sensor for another.






| Gas* / Application Type** | ENV | IAQ | IND | 900 | 930# | SM703 |
|---|-----|-----|-----|-----|------|--------------|
| Ammonia (NH ₃) | | | ✓ | ✓ | * | |
| Carbon monoxide (CO) | ✓ | ✓ | ✓ | ✓ | * | |
| Carbon dioxide (CO ₂) | ✓ | | ✓ | ✓ | | |
| Chlorine (Cl ₂) | ✓ | | ✓ | ✓ | ✓ | |
| Formaldehyde (CH ₂ O) | | | ✓ | ✓ | ✓ | |
| Hydrogen (H ₂) | | | ✓ | ✓ | | |
| Methane (CH ₄) | | | ✓ | ✓ | | |
| Hydrogen sulphide (H ₂ S) | ✓ | | ✓ | ✓ | * | |
| Nitrogen dioxide (NO ₂) | ✓ | | | ✓ | ✓ | |
| Non methane hydrocarbon (NMHC) | ✓ | | | ✓ | | |
| Ozone (O ₃) | ✓ | ✓ | ✓ | ✓ | ✓ | Sensor board |
| Perchloroethylene (C ₂ Cl ₄) | | ✓ | ✓ | ✓ | | |
| Sulphur dioxide (SO ₂) | ✓ | | ✓ | ✓ | ✓ | |
| Volatile organic compounds (VOC) | ✓ | | ✓ | ✓ | * | |

* Refer to the separate gas sensor specification sheet for the full range of sensors.

**Application type: ENV = outdoor environmental monitoring, IAQ = indoor air quality, IND = industrial health and safety.

See sensor type in specification table.

Specifications

| Feature / Series | Series 900 | Series 930 | FM SM70 |
|--|---|---|--|
| Applications | Ozone generator control, indoor air quality, real-time network monitoring, health and safety and process control. | Industrial applications for gas leak detection, real-time network monitoring, health and safety and process control. | Ozone monitor for real-time network monitoring, health and safety and process control. |
| Measurement units | Gas: ppm or mg/m ₃ Optional: Humidity: % a Temperature: °C or °F | | Gas: ppm |
| Reading functions | Instant, minimum, maximum, average | | Instant |
| Sensor head type |  Sensor head Interchangeable |  Sensor head Removable / Replaceable |  Sensor head Removable / Replaceable |
| Sampling method | Active sampling via internal sensor head fan | | Active sampling via sensor board fan |
| Analog output | 4-20 mA (opto-isolated), 10-30 Vdc | 4-20 mA (opto-isolated), 12-24 Vdc | 0-5 Vdc (LZ sensor board), 0-1.5 Vdc (UZ sensor board) |
| External signal type | Transistor output (4) (24 Vdc at 150 mA max) | | Relay output (24 Vdc; 5 A max.) |
| External signal functions | Low Alarm High Alarm Control Diagnostics | | Factory configured |
| External signal input | Standby toggle | | |
| Connectors | Screw type | | |
| Monitor Identification (ID) | 1 (Default) User configurable from 1 to 255 | | |
| Alarm set points | User configurable Low Alarm High Alarm | | Factory configured single point |
| Control set point | User configurable Low Alarm High Alarm | | Factory configured |
| Communication | RS-485 (Aeroqual proprietary protocol) | | RS232 and RS485 (Aeroqual proprietary protocol) |
| Software | Free PC Configuration software and logging Link data to a specific location and monitor (Data cable required) | | |
| Interface (optional) | RS-485 to USB cable | | RS-485 and RS-232 |
| Power (user supplied) | Regulated 12 Vdc, 800 mA | 24 Vdc, 500 mA (range 22-24 Vdc) | 12 Vdc; 800 mA; Plug-in Vdc power adaptor supplied |
| Monitor base/enclosure material and rating | Polycarbonate IP20 NEMA 1 equivalent | Polycarbonate IP41 NEMA 2 equivalent | Flame resistant PS I IP20 NEMA 1 equivalent |
| Size (with sensor head) (L x W x H) | 64 H x 130 Ø mm; 2½ x 5¼ Ø in | 180 x 110 x 90 mm 7¼ x 4¼ x 3½ in | 130 x 94 x 57 mm 5¼ x 3¾ x 2¼ in |
| Weight (Incl. Sensor) | < 200 g; < 7 oz | < 850 g; < 30 oz | 270 g; 9.5 oz (excludes AC power adaptor) |
| Environmental operating conditions | 0°C to 40°C 32°F to 104°F | | |
| Approvals | Part 15 of FCC Rules, EN 61000-6-3: 200, EN 61000-6-1: 2001 | | |

Optional accessories



Temperature/ RH Sensor
FM TRH01



Monitor RS485 to USB Cable
AS R17



Integrated display (930 Only)
FM DISP01



Siren & strobe (930 Only)
AS R23D

